


Liimpuit

Mõõdud

✓ Standard ristlõiked

● Eritellimused

Kõrgus (mm) → Laius (mm) ↓	120	140	160	180	200	220	240	260	280	320	360	400	440	jne tõus + 40mm
60	✓	●	✓	●	✓	●	✓	●	✓	✓				
80	✓	●	✓	●	✓	●	✓	●	✓	✓	✓	✓	✓	
100	✓	●	✓	●	✓	●	✓	●	✓	✓	✓	✓	✓	
120	✓	●	✓	●	✓	●	✓	●	✓	✓	✓	✓	✓	
140		●	✓	●	✓	●	✓	●	✓	✓	✓	✓	✓	
160			✓	●	✓	●	✓	●	✓	✓	✓	✓	✓	
180				●	✓	●	✓	●	✓	✓	✓	✓	✓	
200					✓	●	✓	●	✓	✓	✓	✓	✓	
220						●	✓	●	✓	✓	✓	✓	✓	
240							✓	●	✓	✓	✓	✓	✓	



Pikkused: kuni 36,0 m
Kõrgus: max 2,3 m

Homogeense liimpuidu tugevusklassid, -jäikuse ja -tiheduse väärtused EVS-EN 14080:2013

Tugevusklass		GL24h	GL28h	GL32h
Tugevusomadused N/mm ²				
Paindetugevus	fm,g,k	24	28	32
Tõmbetugevus	ft,0,g,k	19.2	22.3	25.6
	ft,90,g,k	0.5	0.5	0.5
Survetugevus	fc,0,g,k	24	28	32
	fc,90,g,k	2.5	2.5	2.5
Nihke(lõike)-tugevus	ft,0,g,k	3.5	3.5	3.5
Jäikusomadused N/mm ²				
Elastusmoodul	E0,g,mean	11500	12600	14200
	E0,g,05	9600	10500	11800
	E90,g,mean	300	300	300
Nihkemoodul	Gg,mean	650	650	650
Tihedus kg/m ³	rg,k	420	460	490